

Hartell

ISO Certificate

Products


- ▶ **Condensate Pumps**
- Waste Water Pumps
- Ice Machine Pumps
- Circulating Pumps
- Engineered Products

News

Sales

KT-15 Pump

[Purchase Hartell Pumps Online!](#)

KT15 Pump	Features
Supplier & Vendor	ABS PLASTIC RESERVOIR
Reference	THERMALLY PROTECTED,
Milton Roy Americas -	HIGH TORQUE MOTOR WITH
Home Page	300 SERIES S.S. SHAFT
Milton Roy Store (Shirts,	BUILT-IN FULL FLOW CHECK
Hats, etc . . .)	VALVE FOR 3/8" ID PLASTIC
Terms & Conditions	TUBING
How are we doing?	6' POWER CORD WITH
	MOLDED PLUG (NEMA 5-15P or 6-15P)
	12 MONTH WARRANTY

KT15 for up to 15 feet of lift

The KT-15 series condensate pumps lead the industry in quality and economy! The KT-15 is perfect for the majority of residential condensate pump applications. Properly installed, the KT-15 will provide years of trouble free service. All pumps are available with 20' of high quality, clear vinyl discharge tubing (Add the letter "T" to the end of the model designation).

Need the instruction sheet? [Download](#) it online.

SPECIFICATIONS	KT15
MOTOR: (hp @ rpm)	1/20 @ 3000
ELECTRICAL	115V 1.3A 230V 0.9A
INLET SIZE	2 INLETS 1" & 1- 3/8"
DISCHARGE SIZE	3/8" ID
RESERVOIR CAPACITY	3 QUART
UNIT DIMENSIONS (WxDxH)	9.25" X 5.5" X 8.25"
INLET HEIGHT	4.5"
MAXIMUM TEMPERATURE	110° F
SEALED RESERVOIR	NO
WEIGHT	5 LBS

* Width at mounting tabs is 11.25"

PUMP PERFORMANCE	
LIFT (feet)	FLOW (GPH)
5.0	60
10.0	45
13.0	30

MAXIMUM LIFT	15 feet
---------------------	---------

[Return to Top](#)

[View Printable Version](#)